

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

Schilliger Grossformatplatte GFP / Crosslam

according to the product specification listed in the current addendum to this certificate placed on the market by

Company

SCHILLIGER HOLZINDUSTRIE AG

Haltikon 33

CH-6403 Küssnacht am Rigi

and produced in the manufacturing plant

CH-6403 Küssnacht am Rigi, Haltikon 33

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

ETA-19/0675, issued on 31.03.2020

and

EAD 130005-00-0304

under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Certificate number: 1359-CPR-0803

Date of first issue: 30.04.2020

Date of issuance: 30.04.2020


This certificate will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzforchung.at.



DI Bernhard Kraus

Authorised signatory



Dr. Manfred Brandstätter

Head of the Certification Body

Addendum to certificate 1359-CPR-0803

Date of issuance: 30.04.2020

Scope of certification:

Schilliger Grossformatplatte GFP/Crosslam Solid wood slabs to be used as structural elements in Building

| | |
|--------------------------------------|--|
| Structure: | min. 3-layers, layers arranged perpendicular (angle of 90°) 3 parallel layers with a total thickness of 90 mm allowed |
| Strength classes of the laminations: | C 24 according EN 338 |
| Thickness of the laminations: | 9 mm – 50 mm |
| Thickness: | 27 mm - 500 mm |
| Width x length: | max. 3, 4 x 14,0 m |
| Classes of utilisation: | 1, 2 |
| Wood species: | PCAB – spruce /ABAL – fir |
| Adhesive: | |
| - Finger joints: | Type I: PUR according to EN 15425 |
| - Surface bonding: | Type I: PUR according to EN 15425 |